

Covering the globe - world's
only dual-mode 1-meter VSAT

TracPhone® V11IP


One antenna - global coverage

The 3-axis, gyro-stabilized TracPhone V11IP dual-mode onboard terminal uses a single, small, 1.1-meter antenna to seamlessly access both the C- and Ku-band satellites of the mini-VSAT Broadband network for fully global coverage. Unlike competing L-band and Ku-band solutions that require two terminals joined with a router, the TracPhone V11IP is a unified solution: one antenna seamlessly providing both C- and Ku-band services and integrated to one streamlined belowdecks unit.

- 1 Unified C-/Ku-band RF system provides dual-mode capability from one compact antenna
- 2 Highly tuned carbon-fiber dish paired with a custom LNB using KVH's exclusive RingFire™ technology ensures superior reception
- 3 Advanced modular antenna controller for high-speed tracking
- 4 3-axis pedestal design with a 4th axis of automatic skew adjustment seeks the optimal satellite in the mini-VSAT Broadband network and tracks satellites directly overhead at the equator and low on the horizon at polar latitudes
- 5 Robotic, direct-drive, beltless motion control



All VIP-series products include KVH's new **Integrated CommBox Modem (ICM)** with IP-enabled antenna control unit, CommBox™ Network Manager, ArcLight® spread spectrum modem, Voice over IP, Ethernet switch, and Wi-Fi capabilities. Systems also feature a browser-based user interface and convenient iPhone® app for system status, updates, and support.



System Specifications

Service	
Network	mini-VSAT Broadband
Antenna Type	Dual-mode C-/Ku-band
Service Coverage Area	Global except Arctic Regions
Maximum Speed Download/Upload ¹	4 Mbps/1 Mbps
Above-decks Equipment	
Antenna Dish Diameter	1.1 m (42.5")
Antenna Unit Dimensions/Weight	1.2 m D x 1.4 m H (48.8" D x 57.3" H) / 109 kg (240 lbs)
Elevation/Azimuth Range	-24° to +119° / 720° rotation
Temperature	Operating: -30°C to 55°C (-22°F to 131°F) Survival: -30°C to 70°C (-22°F to 158°F)
Humidity	IEC 60945; 40°C (104°F), 95% Humidity (non-condensing)
Rain	Precipitation rate of 100L/Min, w/wind speeds up to 100 knots
Heading Input	NMEA 0183 magnetic or true heading
Antenna Unit Power	100-240 VAC, 50-60 Hz auto switching, 500 watts; provided at the dome
ICM to Antenna Unit Communications	16 Conductor Data Cable
L-band RF Cables (customer supplied)	75 Ohm – F-Connector terminations; For 5.8-30.5 m (16-98 ft.) choose LMR-400-75 For >30.5-91.4 m (98-295 ft.) choose LMR-600-75
Remote Support	Integrated GPRS modem for access by KVH technical support
Below-decks Equipment – Integrated CommBox Modem (ICM)	
Dimensions	42.6 cm (l) x 41.4 cm (w) x 2U (h) (16.8" x 16.3" x 2U) rack-mountable with optional mounting provisions ²
Weight	5.1 kg (11.25 lbs)
Temperature	Operating: -15°C to 55°C (5°F to 131°F); Survival: -15°C to 70°C (5°F to 158°F)
Input Power	100-240 VAC, 50-60 Hz auto switching, 1.6 A max
Data Interfaces	4 Ethernet: IEEE 802.3 10BASE-T/100BASE-TX, 100 Mbps; 1 Wi-Fi 802.11; 3 USB ports
Voice Interfaces	2 RJ11 ports for VoIP services
System Options	
CommBox Software Bundles Available	Standard or Enterprise Packages - see "Featured Options" at kvh.com/V11iP for details
Built-in Crew Calling Gateway	Available; contact Airtime Services for details
IP-MobileCast™ Services	Coming soon; contact KVH for details
UCH-250 Fax Server	For enterprise-grade faxing over IP (P/N 19-0520); contact KVH for details
GlobalCare Premium Support Program	Available; see kvh.com/globalcare for details
Iridium Pilot Secondary System	Available (P/N: 72-0537-01); see "Featured Options" at kvh.com/V11iP for details
Complete System	
Certification	Complies with the specifications of EC directive 1999/5/EC Radio & Telecommunications Terminal Equipment (R&TTE), per compliance with EC directive 2006/95/EC, EMC directive 2004/108/EC and IEC 301-427
System Warranty ³	Comprehensive 2-year parts, 1-year labor warranty supported by KVH's worldwide Certified Support Network (CSN)
Part Number / MSRP (USD)	01-0350-11 / \$74,995

Meets FCC and CE requirements. Exceeds Inmarsat operational, survival, and shock specifications.

¹Published data speeds are maximum speeds and may vary in different regions and under different conditions.

²Optional Belowdecks Mounting Case (KVH Part No. 72-0368) available for vessels without a rack.

³Unless subject to in-country regulations. Restrictions apply. Visit www.kvh.com/warranty for details.


System Diagram



Integrated CommBox Modem (ICM) – Streamlined belowdecks unit includes: IP-enabled antenna control unit, built-in CommBox Ship/Shore Network Manager, ArcLight spread spectrum modem, Voice over IP (VoIP), Ethernet switch, and Wi-Fi capabilities.



85% smaller in volume and lighter than standard C-band antennas, TracPhone V11iP is faster, easier, and less expensive to install.



mini-VSAT Broadband C-/Ku-band Coverage

Coverage maps are representative and may change at any time. Data rates may also vary in different regions. For complete details, choose "TracPhone" at www.kvh.com/footprints and click on the mini-VSAT Broadband coverage map. KVH provides no guarantees of satellite coverage or availability.

- Ku-band Coverage with C-band Overlay Coverage
- Ku-band Coverage
- C-band Coverage



KVH Industries A/S
 EMEA Headquarters
 Kokkedal, Denmark
 Tel: +45.45.160.180 Fax: +45.45.160.181
 Email: info@emea.kvh.com

KVH Industries, Inc.
 World Headquarters
 Middletown, RI U.S.A.
 Tel: +1.401.847.3327 Fax: +1.401.849.0045
 Email: info@kvh.com

KVH Industries Pte Ltd.
 Asia-Pacific Headquarters
 Singapore
 Tel: +65.6513.0290 Fax: +65.6472.3469
 Email: info@apac.kvh.com